

# **Grant County**


## **PUBLIC WORKS DEPARTMENT**

Derek Pohle, P.E.  
Director of Public Works and  
County Road Engineer  
Ephrata (509) 754-6082

David N. Heilman  
Assistant Director of Public Works  
and County Road Engineer  
Ephrata (509) 754-6082

Todd Mittge, P.E.  
Assistant County Road Engineer  
Ephrata (509) 754-6082

Robert Bersanti  
Design/Construction Engineer  
Ephrata (509) 754-6082



124 Enterprise St. S.E.  
Ephrata, Washington 98823  
(509) 754-6082; Fax (509) 754-6087

Steve Hill, Supervisor  
Road District No. 1  
Ephrata (509) 754-6586

Dennis Collier, Supervisor  
Road District No. 2  
Moses Lake (509) 765-4172

John Brissey, Supervisor  
Road District No. 3  
Quincy (509) 787-2321

Jerome Wawers, Supervisor  
Bridges  
Ephrata (509) 754-6082

Janice Goeden  
Solid Waste Supervisor  
Ephrata (509) 754-4319

Sealed bids will be received for the following equipment:

### **Dump Trucks**

Bid Opening  
at

**2:00 PM**

**January 8, 2013**

at the

Office of the  
Board of County Commissioners  
Grant County Courthouse  
35 C Street NW, Room 207  
P.O. Box 37  
Ephrata, WA 98823

**Informational Copy Only - NOT FOR BIDDING**  
Call 509-754-6082 to obtain Bid Package

## NOTICE TO EQUIPMENT DEALERS

Sealed bids, plainly marked "**Bid for Dump Trucks, Equipment Contract 2013-02**", will be received by Grant County at the Office of the Board of County Commissioners located in the County Courthouse, 35 C Street NW - Room 207, P.O. Box 37, Ephrata, WA 98823, until **2:00 PM, Tuesday, January 8, 2013**, and will then and there be opened and publicly read for furnishing and delivering:

<u>Item #</u>	<u>Quant.</u>	<u>Description</u>
1	2	450 hp Chassis & 14 cy Dump Body w/12' 2-way Plow and 10 cy Body Sander

Informational copies of the proposal and specifications are on file with the County Engineer in the Grant County Public Works Building, 124 Enterprise St. S.E., Ephrata, WA 98823.

Any bidder offering new equipment shall include in their proposal an offer to purchase the trade-in equipment. The County assumes the new equipment bidder's trade-in offer is a part of the bid including the new equipment. The bidder's trade-in offer will only be considered separately if the bidder grants permission to the County to consider their trade-in offer separately.

Any person or company may make an offer to purchase the trade-in equipment independent of a bid on the sale of the new equipment. Such offers shall be made on forms provided by the County. The bidders are advised that mileage/hours will continue to accumulate at the current usage rate until replacements vehicles are delivered. The County is offering the following trade-ins:

Trade-Ins:

### **#1330 - 1991 Ford LT9000 w/Henke two-way 12' snow plow & Monroe 15' body sander**

VIN No. 1FDYU90XXMVA25887 License No. 15871C Mileage as of 12/18/12: 254,238  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A transmission, 20,000 lb. front axle, 23,000 lb. rear axle, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated air dryer, 54,400 gvw, Color: Red

This chassis is equipped with a Monroe 15' sander body, and a Henke two-way 12 ft snow plow.

The chassis, sander and plow may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

### **#2160 - 1997 Ford LN8000 w/4 cy Thermolay Asphalt Patcher**

VIN No. 1FDYR82E1VVA03981 License No. 37848C Mileage as of 12/18/12: 81,813  
Cummins 8.3L 6 cyl. diesel engine (210 hp), Fuller 10 speed RT7608LL transmission, 12,000 lb. front axle, 23,000 lb. single rear axle, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated air dryer, 35,000 gvw, Color: Red

This chassis is equipped with a 4 cy Thermolay Asphalt Patcher and Spreader.

The chassis and patcher may be inspected at Dist 2 Shop in Moses Lake, WA., 12171 Road 3 NE, Monday through Thursday between 10:00 am and 3:00 pm. (509) 765-4172

### **#3300 - 1991 Ford LT9000 w/Heil 10 cy dump body**

VIN No. 1FDYU90X8MVA25886 License No. 15877C Mileage as of 12/18/12: 293,564  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A transmission, 20,000 lb. front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and right sides, 162"

wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated air dryer, 54,400 gvwt, Color: Red

This chassis is equipped with a Heil 10-12 cy dump body.

This chassis and dump body may be inspected at Grant County Landfill in Ephrata, WA., 3803 Neva Lake Rd NW, Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-4319

**#3510 - 1998 Peterbilt 357 w/Crysteel 12 cy dump body, Henke EXP two-way 11' snow plow**

VIN No. INPALB9X-3-WD446791 License No. 43786C Mileage as of 12/18/12: 236,447  
Cat 3406-E 6 cyl. diesel engine (355 hp), Fuller RTLO-14713A 13 speed transmission, 20,000 lb. front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated air dryer, 54,600 gvwt, Color: Red

This chassis is equipped with a Crysteel 12 cy dump body, a Monroe 15' sander body, and a Henke two-way 12 ft snow plow.

The chassis, dump body and plow may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**#034 - 1985 International Harvester Cargostar 1950B-DT466 w/Line Striper**

VIN No. 2MTNGUXR3FCB10318 License No. 15824C Mileage as of 12/18/12: 214,792  
International Harvester DT466 diesel engine, 466 CID (210 hp), T448 10 speed transmission, cabover, one 70 gal. fuel tank, 164" wheelbase, 146" cab/axle, 32,000 gvwt, Light Green, 11R22.5 tires front and rear. Color: Lime Green

This chassis is equipped with a 3 nozzle Line Striper, an auxiliary John Deere 4239 DF 4 cylinder diesel engine, 325 gallon paint tanks, 2400 lb glass bead tank, two Vicom cameras with cab monitor.

The chassis and line striper may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

All equipment is offered "AS IS". Prospective buyers may view the equipment at the convenience of the operator. Please call the department to make arrangements to inspect the vehicle. All equipment is operating and currently in-service.

The Board of County Commissioners reserves the right to reject or accept any or all portions of the bids received.

## INSTRUCTIONS TO BIDDERS

- 1) Sealed bids, plainly marked **"Bid for Dump Trucks, Equipment Contract 2013-02"**, will be received by Grant County at the Office of the Board of County Commissioners located in the County Courthouse, P.O. Box 37, 35 C Street NW - Room 207, Ephrata, WA, 98823, until **2:00 PM, January 8, 2013**, and will then and there be opened and publicly read for the construction of the improvements.
- 2) The Bidder may submit a bid on any or all items listed. If the Bidder does not wish to bid any particular item or items, please write **"NO BID"** on the appropriate proposal sheet.
- 3) Multiple bids for the same item may be made by the Bidder. Please copy the appropriate proposal sheet(s) for the item(s) to be bid with more than one model. The proposal for each item bid must be completed. Please number the proposal sheets accordingly.
- 4) The proposal must be completed and the proposal signature sheet must be signed.
- 5) An informational copy of the contract is provided to the Bidder. Please read it but do not sign it.
- 6) All exceptions or changes to the specifications must be shown on the proposal sheet(s) in the space provided or attached to the proposal sheet.
- 7) The Board of County Commissioners reserves the right to reject or accept all or part of the proposal submitted by the Bidder.
- 8) Bidders are advised that the unit price bid for each new item will be compared with current State or other public agency contract prices for similar vehicles. After said comparison the County may reject or accept all or part of the proposal submitted by the Bidder and purchase items directly from the State or other public agency contracts.
- 9) Trade-in equipment is offered for sale in this contract. Bidders offering new equipment are required to make an offer on the trade-in equipment listed, but can choose to restrict their offer to the award of the contract. Interested parties that are not offering new equipment may submit a bid for one or more trade-in equipment listed. A 5% bid security is required for offers made on all trade-ins from bidders not offering new vehicles or equipment. Although no minimum bids are reserved the County will compare trade-in offers to reliable publications or other sources.

Interested parties bidding for trade-in equipment only are required to post a 5% deposit based on the bid amount offered for the equipment. The deposit will be held until the purchaser provides the whole amount for all vehicles awarded to the high bidder. If the purchaser fails to pay for the awarded vehicles within the allotted time, the deposit shall be forfeited to the County.

**Informational Copy Only - NOT FOR BIDDING**  
Call 509-754-6082 to obtain Bid Package

**PROPOSAL - PART I**  
(For New Equipment Dealers)

**General Conditions**

1. The attached specifications are for the purpose of providing details regarding the type of product desired by Grant County. Equal or similar products from reputable manufacturers and suppliers are permitted. Grant County shall be the final determiner of product equivalence.
2. Bidders interested in providing bids for new equipment must complete and return Part I of this proposal.
3. The Bidder has 15 days from the date of award to sign and return the contracts. Failure to sign and return the contracts may result in the loss of the contract to the Bidder. No performance bond is required for this bid proposal.
4. Grant County shall pay State sales and use taxes on all products purchased. The Bidder shall not include taxes in the bid price and shall show state sales taxes as a separate item in the space provided.
5. Grant County is a political subdivision of the State of Washington and is exempt from paying all Federal excise taxes. The Bidder shall furnish Federal excise tax exemption certification when applicable. All other taxes and costs of business shall be borne by the Bidder and included in the base price offered.
6. The bidders are advised that mileage/hours on used equipment will continue to accumulate until replacement vehicles/equipment are delivered.
7. All products shall conform to applicable Federal and State safety and health laws, rules and regulations.

**Bid Evaluations**

1. Bid evaluations shall include, but not be limited by, the following criteria:
  - Price (*may include life cycle*)
  - Quality of product
  - Conformance to specifications
  - Prompt service and parts availability
  - Training
  - Bidder's previous contract experience
  - Public's best interest.

**Submissions to be included with the Bid Proposal**

1. Bidders are advised to submit the following with each bid item:
  - Descriptive literature.
  - Complete operating dimensions and sketches of the proposed unit.
  - Complete information detailing engines, engine accessories, transmissions, frame, axles, electrical components, cab, differentials, drivelines, hydraulic systems, and appurtenances for each unit bid.
2. The Bidder may submit any other information that may assist Grant County in evaluating the bid.

### **Full Service Facility**

A full service facility is defined as the location with spare parts available to Grant County within 24 hours from 8:00 AM to 5:00 PM, Monday thru Friday.

### **Warranty**

The Bidder must state the warranty period(s) on all items bid or portions of each item. Grant County may require a minimum warranty period. Within the warranty period the successful Bidder shall replace all parts and perform all repairs which are required or made necessary due to defective design, materials, workmanship, or non-conformance with the specifications. Unless otherwise noted, the Bidder shall perform all warranty repairs at the Bidder's place of business. Grant County shall deliver and retrieve defective equipment at the Bidder's place of business. All repairs shall have the warranty reinstated for the remaining period.

### **Operator's, Parts and Service Manuals**

The Bidder shall furnish operator's manuals, service manuals and parts manuals as specified in the proposal. **Manuals must be delivered to Grant County before product delivery is considered complete.**

### **Delivery, Inspection and Acceptance**

All equipment shall be new and the manufacturer's latest model. All standard equipment shall be furnished with the unit. The unit and mounted equipment, if any, shall be serviced, comply with all specifications, and be in full working order for the purpose it was designed at the time of delivery.

**Grant County will accept delivery between the hours of 8:00 AM to 3:30 PM, Monday thru Thursday only.** Unless otherwise noted, deliveries shall be F.O.B., Freight and Insurance Prepaid and Included, to Grant County. The Bidder will be required to obtain a delivery address within Grant County, Washington, and the time from the County Engineer, or his designated representative, for each piece of equipment. The Bidder, or his representative, is requested to be present at the time of delivery.

Supplier(s) shall provide the following documents for review at time of delivery for each item.

- The manufacturer's line production sheet stating the equipment serial and identification numbers and listing all of the equipment's components. (Maroni sticker)
- Completed Invoice.
- The Manufacturer's Statement of Origin (MSO).
- Axle weight slips (for all units with axles).
- A completed Washington State title application showing both the legal and registered owner as: Grant County Public Works, 124 Enterprise St. SE, Ephrata, WA 98823. The mailing address is the same. Out of state Supplier(s) may contact Grant County, Financial Administration Office at (509) 754- 6082 to obtain a Washington State title application.

### **Training**

1. The Bidder and manufacturer's representatives must be able to provide sufficient training to Grant County personnel to operate, service and repair the equipment. The training should occur in Grant County. Training shall include all labor, equipment, materials, tools, travel and other expenses needed to provide a complete service. The Bidder may show a minimum number of training hours for each category. Failure to offer any training will be a consideration in the bid evaluation process.
2. The Bidder shall state the number of hours and the cost per hour for each category of training on the proposal form in the space provided.



3. Training is an additive cost to the contract. The Bidder shall not include training costs in the base bid of the proposal. Grant County is not obligated to use the training offered by the Bidder, however, should Grant County desire to utilize the training programs offered those costs will be added to the contract..

**Late Delivery**

No penalty for late delivery will be assessed against the Bidder. However, the Bidder is advised that the failure to deliver the equipment before the promised date will be a consideration used at succeeding bid proposal evaluations.

**Trade-ins**

Grant County is not obligated to accept any trade-in offer and may accept new equipment bid without the required trade-in offer. The trade-in offer itself will be considered to be a part of the whole item and will not be considered separately unless the bidder checks the appropriate line. Bidders wishing to bid for trade-ins only to be considered separately should complete and sign Part II of this proposal and provide a 5% security deposit. No security deposit is required for bidders bidding new equipment and offering trade-in values in Part I of this proposal.

Informational Copy Only - NOT FOR BIDDING  
Call 509-754-6082 to obtain Bid Package

**Informational Copy Only - NOT FOR BIDDING**  
Call 509-754-6082 to obtain Bid Package

**PROPOSAL Bid Item No. 1**

BID ALTERNATE # \_\_\_\_\_

<u>Description</u>	<u>Quantity</u>	<u>Unit Price</u>	<u>Amount</u>
Furnish and deliver :			
..... <b>truck chassis</b> .....	2.....	\$ .....	\$ .....
F.O.B. Grant County, WA		Trade-in #1330	(\$ .....)
		Trade-in #2160	(\$ .....)
		Trade-in #3300	(\$ .....)
		Trade-in #3510	(\$ .....)
		Trade-in #034	(\$ .....)
Note: Bidder agrees to let the County consider trade-in offers separately:		Subtotal	\$ .....
Yes _____ No _____		% SST	\$ .....
(Please check one)		Total Chassis Bid	\$ .....
Chassis equipment:			
..... <b>12-14 cy dump body</b> .....	2.....	\$ .....	\$ .....
..... <b>12' two-way snow plow</b> .....	2.....	\$ .....	\$ .....
..... <b>10 cy body sander</b> .....	2.....	\$ .....	\$ .....
F.O.B. Grant County, WA		% SST	\$ .....
		Total Equip. Bid	\$ .....
		Total Bid	\$ .....

**Extended Purchase Options:**

*(The bidder is requested to provide extended purchase order information. If no extended purchase bid is offered, please write NO BID in the spaces shown)*

Please list final order date for 2013 model purchase orders. .... Chassis \_\_\_\_\_  
 \_\_\_\_\_ Dump Body \_\_\_\_\_  
 \_\_\_\_\_ Snow Plow \_\_\_\_\_  
 \_\_\_\_\_ Body Sander \_\_\_\_\_

Please list the additional amounts for purchases requested after the final order date listed above and on or before February 15, 2014 .... Chassis \$ \_\_\_\_\_  
 \_\_\_\_\_ Dump Body \$ \_\_\_\_\_  
 \_\_\_\_\_ Snow Plow \$ \_\_\_\_\_  
 \_\_\_\_\_ Body Sander \$ \_\_\_\_\_

Bidder is required to provide the following information:

Make and Model Cab/Chassis: _____	Delivery: _____
Warranty Period (engine): _____	(After receipt of order)
Warranty Period (transmission): _____	
Warranty Period (cab/chassis): _____	
Make and Model Dump Body: _____	Delivery: _____
Warranty Period: _____	(After receipt of order)
Make and Model Snow Plow: _____	Delivery: _____
Warranty Period: _____	(After receipt of order)
Make and Model Body Sander: _____	Delivery: _____
Warranty Period: _____	(After receipt of order)

### Truck Chassis Specifications:

The selected bidder is expected to furnish, install and deliver a cab and chassis designed for use with a dump body, trailer towing, two-way snow plow and body sander. This specification references the Western Star 4900FA .

#### General

#### List specifications, models & cost changes

- 2013 model year severe duty cab and chassis
- 64,000 lb. gvw
- Maximum road speed 65 mph
- Ambient air temperatures from -20°F to 110°F in the Columbia Basin region of Washington State
- Expected highway grades at 8%
- Conventional cab @ 124"± BBC with sound suppression package and vibration isolation
- 12 cubic yard pup trailer towing provisions
- 122" back of cab to center of rear tandem axle, 57" frame overhang, 90"± front axle to back of cab, 212"± wheelbase
- Set forward axle
- 12 cubic yard (struck) dump body
- Special hitch plate
- 12' two-way snow plow with universal quick hitch
- 10 cy body sander
- All hydraulic connections must terminate with quick disconnect flush face (minimum spill) couplers and must be clearly and permanently labeled. Couplers must meet following specifications:  
1/2" male/female - Parker FF-502-8FP/Parker FF-501-8FP  
3/4" male/female - Parker FF-752-12FP/Parker FF-751-12FP  
1" male/female - Parker FF-1002-16FP/Parker FF-1001-16FP

#### Engine

- **Base Engine:** Cummins ISX15 450 4-stroke 6 cylinder turbocharged diesel engine, 450 hp, 1650 lb-ft torque @ 1200 rpm. This engine is EPA compliant with 2013 emission standards.
- Full 2 yr/250,000 mile engine warranty.
- **Option 1 Engine:** Detroit Diesel DD15 4-stroke 14.8 liter 6 cyl. turbocharged diesel engine, 455 SAE net HP @ 1,800 rpm and 1,650 lb-ft torque @ 1,100 rpm. This engine is EPA compliant with 2013 emission standards  
(Please show cost difference for this option) \$
- Full 2 yr/250,000 mile engine warranty.
- Full engine retarder, exhaust brake
- Magnetic fill/drain plugs
- Full flow spin-on oil filter
- Additional cost for full five (5) year engine warranty \$ Cummins \$ Detroit

#### Engine Compartment

- 1,375 cubic inch radiator, brass/copper, with auto. fan clutch (Provide larger radiator if recommended by engine mfg.)
- Engine coolant w/ethylene glycol protected to -60°F, filter
- 120v 1,500 watt emersion block heater, easy access receptacle
- Heavy duty dry-type single-stage air-cleaner, mounted under hood
- Passive ejector/prescreener for dust and snow
- List alternate auto ejector for dust and snow, including price \$
- Power steering

- 12 volt electrical system with 130 amp alternator internally regulated
- Three (3) 12 volt maintenance free batteries, 3300 CCA
- Frame mounted battery box, external posts for jump start, painted steel
- Bendix 16.5 cfm air compressor, heated air drier, spin-on filter
- 2,000 cubic inch steel compressed air reserve tank(s)
- Automatic fan control with dash switch and indicator light
- Spin on fuel filter
- Access for crankshaft PTO, pass-through radiator for pump, mounted on front frame extensions

#### Transmission

- **Base Transmission:** Eaton Fuller RTLO-16918B 18-speed overdrive manual transmission
- **Option 1 Transmission:** Eaton Fuller FO-16E318B-MXP 18-speed Ultrashift Plus automated transmission  
(Please show added cost for this option) \$
- External transmission oil cooler, frame mounted
- Transmission leaf spring support
- Magnetic fill/drain plugs
- Eaton Fuller 15-½" clutch, manual adjustment, 1,650 ft-lb, cast iron housing
- Full warranty period, please state in time and mileage
- Additional cost for full five (5) year transmission warranty \$

#### Frame, brakes, axles, suspension and tires

- Steel frame and insert per manufacture's design for vocational Class 8 severe duty use. Please list base frame, options with price changes

- 24 " integral front frame extensions
- 16.5" x 6" front cam brakes with dust shields, cast iron drums, auto slack adjusters, wet-type oil seals
- 16.5"x7" rear cam brakes with dust shields, cast iron drums, auto slack adjusters, oil seals
- Anti lock brake system Wabco 4 sensor/4 modulator with trailer warning light
- Spring actuated emergency brakes effective on all axles and capable of holding fully loaded vehicle on 10% grade
- 20,000 lb. front axle
- 18,000 lb. front leaf suspension with double-acting shock absorbers
- 22.5 x 9.00 front steel wheels, white, 10 hole stud-piloted (Budd type)
- 315/80R 22.5L 20 ply (9000 lb. single load) radial front tires Michelin XZY-3 or other brand equivalent
- No additional front spare tire and wheel required
- 46,000 lb. rear axles
- 52" rear axle spacing
- 46,000 lb. rear suspension, Hendrickson RTE 463 with shock absorber kit
- 22.5 x 8.25 RR steel wheels, white, 10 hole stud-piloted (Budd type)

- 11R 22.5G 14 ply (5,850 lb dual load) rear tires, Michelin XDE or other brand equivalent, 8 tires
- No additional rear spare tire and wheel required
- 4.30 rear axle ratio, magnetic traps and drain/fill plugs
- Driver controlled differential lockup, both axles on tandem

#### Chassis Equipment

- Area between chassis frame rails and from the back of cab to 48" rearward of back of cab must remain clear of all air tanks, oil coolers, hydraulic systems, etc., to provide access for sander discharge chute
- One 100 gallon fuel tank mounted on driver's side of truck, two full length slip-resistant steps on fuel tank for access to cab. Two 50 gallon tanks w/steps acceptable
- One 23 gallon diesel exhaust fluid tank
- Single bright chrome vertical exhaust stack, curved top, stainless steel shield, mounted passenger side of cab, 11'± high, muffler mounted horizontal. Coordinate installation with dump body half-cab protector
- Air lines for trailer towing including gladhands, unmounted
- Trailer cable, J560 7-pin receptacle, center pin powered thru ignition, unmounted, incl. chassis power distribution module
- HD steel front bumper, painted black
- Bumper mounted tow hooks
- License plate mounting bracket on bumper
- Front mud flaps mounted to chassis, splash guards mounted to hood, black
- Rear mud flaps, mounted to chassis frame, fore and aft of tandems, black

#### Cab Equipment - Exterior

- Cab vibration isolation and sound suppression package
- Dual air horns, electric horn
- LH/RH extended grab handles
- Bug screen, grille mounted
- Doors and ignition keyed alike, provide three sets per truck
- Switch and wiring for high-mount headlights, turn signal and side marker lights used above snow plow. Provide receptacle on hood near tilt pin, allow for hood tilt. Coordinate installation of high-mount headlights, turn signals and side marker lights on cab with snow plow provider to provide clear sight distance with plow mounted. Plow provider shall furnish and install high mount headlights with turn signals and side marker lights
- Switch w/indicator lamp and wiring for utility light behind cab, provide receptacle and light on back of cab
- LED stop/tail/turn signal and backup lights
- LED side and top of cab marker lights switched through chassis circuits
- Stainless steel mirrors, 16" x 8", heated, RH remote controlled
- Stainless steel auxiliary mirrors, 8", mounted below primary
- Rear cab window
- Corner cab windows
- Passenger side lower door window

#### Cab Equipment - Interior

- Factory installed air conditioning/heater/defroster systems
- Tinted windows

- LH/RH door trim with storage pockets for operator's manual and log book
- AM/FM/Weatherband stereo radio w/single CD
- Overhead console with 12 v power and antenna access port for customer installed two-way radio (CB package)
- Bluetooth for hands-free cell phone use, wired through sound system (customer to provide phone)
- All standard analog system gauges, warning lights and chimes (attach list)
- All standard digital monitoring and diagnostic systems, warning lights and chimes (attach list)
- Fuel level gauge
- Diesel exhaust fluid gauge
- Hour meter
- Outside air temperature gauge
- Tinted windows
- Backup alarm with volume level positions
- Four (4) extra 12 volt circuits with dash mounted switches with indicator lamps (upfitter switches)
- Marker lights and headlight switch with separate interrupter and terminals for snow lights
- Auto self-resetting circuit breakers
- Wiring schematics
- Convenience lighting group
- Rubber floor mats
- Two cup holders with size inserts
- Air suspension driver's seat, HD cloth, with retractable dual armrests, adjustable position and height with adjustable lumbar support, 3 point seat restraint system
- Vinyl passenger bench with largest available tool box
- 20# Type ABC fire extinguisher
- Telescoping steering wheel with tilt
- Cruise control
- 18" cushioned steering wheel
- LH/RH sun visors
- Trailer brake hand control valve

#### Color

- Color: Exterior - Imron Color Code N2225 (Candy Apple Red)
- Interior - Dealer selected
- Manufacturer's standard for all other components that are not rubber, aluminum or bright finished

#### Standard Equipment and Warranty

- All factory standard equipment and warranties including: two parts books, two shop manuals, and two operator's manuals to be furnished at the time of delivery. Manuals furnished on CDs is preferred.
- Full 12 month service and repair warranty for cab/chassis
- List other factory standard equip. warranties or attach literature

Nearest service outlet for **engine** warranty repairs:

Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
Street: \_\_\_\_\_ Phone: (\_\_\_\_) \_\_\_\_\_  
City: \_\_\_\_\_ Fax: (\_\_\_\_) \_\_\_\_\_  
State: \_\_\_\_\_ Zip \_\_\_\_\_ Email: \_\_\_\_\_

Proposed customer training:

Operator..... hrs @ \$ \_\_\_\_\_/hr  
Service..... hrs @ \$ \_\_\_\_\_/hr  
Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
Location..... \_\_\_\_\_

Nearest service outlet for **transmission** warranty repairs:

Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
Street: \_\_\_\_\_ Phone: (\_\_\_\_) \_\_\_\_\_  
City: \_\_\_\_\_ Fax: (\_\_\_\_) \_\_\_\_\_  
State: \_\_\_\_\_ Zip \_\_\_\_\_ Email: \_\_\_\_\_

Proposed customer training:

Operator..... hrs @ \$ \_\_\_\_\_/hr  
Service..... hrs @ \$ \_\_\_\_\_/hr  
Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
Location..... \_\_\_\_\_

Nearest service outlet for **cab/chassis** warranty repairs:

Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
Street: \_\_\_\_\_ Phone: (\_\_\_\_) \_\_\_\_\_  
City: \_\_\_\_\_ Fax: (\_\_\_\_) \_\_\_\_\_  
State: \_\_\_\_\_ Zip \_\_\_\_\_ Email: \_\_\_\_\_

Proposed customer training:

Operator..... hrs @ \$ \_\_\_\_\_/hr  
Service..... hrs @ \$ \_\_\_\_\_/hr  
Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
Location..... \_\_\_\_\_

**Dump Body Specifications**

The selected bidder is expected to furnish and install a dump body and special hitch plate with all required controls and hydraulic systems for dump body, hitches, plow and sander. The dump body must be dismountable. (See attached plan)

- 2013 model year \_\_\_\_\_
- 14 cubic yard capacity (heaped with side boards) \_\_\_\_\_
- 15' 6" ft. box length, 7 ft. box width, 34"± sidewall height, 46" tailgate height \_\_\_\_\_
- 8 gauge one-piece high tensile steel sidewalls and headwall. Flanged top rail and sloped braces. Gussets for 3" wide side board extensions \_\_\_\_\_
- 1/4" thick T1 abrasion resistant steel floor supported with 8 gauge interlaced bracing 20" c/c, or equivalent \_\_\_\_\_
- 4" x 45° knee braces along sidewalls and headwall (excluding doghouse) \_\_\_\_\_
- 10 gauge x 24" steel half-cab protector, 1:12 slope toward box, 2" lip on edges. Provide cut-away for vertical exhaust \_\_\_\_\_
- Box mounted with a 12" min. overhang beyond chassis frame \_\_\_\_\_
- 10 gauge high tensile steel tailgate, horizontal brace, spreader chains \_\_\_\_\_
- Asphalt tailgate \_\_\_\_\_
- Air-actuated tailgate release/capture with cylinder, switch mounted on air control console with position indicator \_\_\_\_\_
- Inspection plate at top of doghouse \_\_\_\_\_
- Seven (7) slip resistant bar steps (four outside/three inside) and one vertical extended hand hold welded to box providing ingress & egress to box by driver's door \_\_\_\_\_
- Tire chain hooks, four each side \_\_\_\_\_
- LED oval stop/tail/turning lights, LED oval side turning signals, and LED round side and tailgate makers markers. All lights housed in rubber setshock containers. FMVSS 108 compliant \_\_\_\_\_



- Whelen L31Super LED 360° Beacon attached to half-cab protector. Use available chassis upfitter switch, provide required fuse (not circuit breaker), connect highest pulse flash pattern w/high intensity feature
- Wiring encased in non-rusting conduit
- Air-actuated pintle hitch activated when parking engaged
- Hitch panel and drawbar to be built in substantial compliance with the attached plan
- Heil HPT 63-130 three stage front mounted hoist, or equal, with 12" overhang (end of frame), 38 ton lift capacity, 50° dump angle, hydraulic feed lines at top of base cylinder, air bleed valve at top of third stage. Slow elevation and return speeds will not be acceptable
- Mounted hoist frame and bolts must be independent from mounted frames and bolts for battery box, valve platform, and hydraulic tank. Mounted hoist frame must bolt to top of angle steel bolted to outside truck frame. Hoist frame mounted inside of chassis frame rails will not be acceptable because of conflicts with body sander discharge chute
- Crankshaft mounted PTO with pressure compensating gear pump, 35 gpm @ 2000 rpm
- Relocate chassis air tanks as necessary to accommodate installation of hydraulic control valve assembly
- Commercial Intertech VA35 five (5) section control valve mounted outside of cab, with #16 O-Ring Boss ports, relief for spike protection. Outlet to have #20 ORB ports. Electric and electric over air controls to be mounted on air control console close to the operator. Provide controls for all components: main dump body (lift, hold & gravity drop), pup dump body (lift, hold & gravity drop), plow (lift, hold & restricted gravity drop), plow angle (left to right, infinitely variable angles), equipment trailer (On/Off supply for trailer functions), sander spinner and conveyor (On/Off), main dump box tailgate hitch, pup dump box tailgate hitch. Controls for levers shall have proportional control for feathering. Controls shall be backlit or handle lit, lighted for "ON" position. Coordinate the work with other suppliers  
Controls shall be permanently labeled (stickers not acceptable)  
Valve 5 (3 way): Raise dump body (gravity down) with interlock Part No. VM431N0101S or equal  
Valve 4 (3 way): Raise pup trailer dump body (gravity down) or operate equipment trailer systems (i.e. traveling axle/tilt equipment trailer/winch)  
Valve 3 (3 way): Raise snow plow (gravity down with flow restriction to prevent drop)  
Valve 2 (4 way) Port A: Plow shift clockwise  
Valve 2 (4 way) Port B: Plow shift counterclockwise  
Valve 1 (4 way series section) Port A: Sander supply to two-valve system, 1200 psi relief  
Valve 1 (4 way series section) Port B: Sander return and equipment trailer return  
Spool operators shall be supplied by valve manufacturer  
Air cylinders to be repairable without taking valve apart
- Cylindrical 50 gallon hydraulic oil reservoir, Mobile Equipment Systems Part #A3500-3-ST, 1-800-354-9028, with hydraulic return filters, suction strainer, sight gauge and filler breather cap. Mount on outside of chassis frame so as not to interfere with dump box and sander operations, painted black

- Control valve assembly mounted on outside of chassis frame so as not to interfere with dump box and sander operations \_\_\_\_\_
- All hydraulic connections must terminate with quick disconnect flush face (minimum spill) couplers and must be clearly and permanently labeled. See attached plan for Parker part numbers for 3/4" and 1 " flush face quick couplers. At the hitch mount male couplers on the supply side (driver side) and female couplers on the return side (passenger side). \_\_\_\_\_
- All electrical wiring and components must be mounted, sealed, and fastened to prevent damage or failure due to vibration, rubbing, moisture, and temperature variations \_\_\_\_\_
- Color: Imron Code N2225 - Candy Apple Red \_\_\_\_\_
- All factory standard equipment and warranties including:  
Three parts books, three shop manuals, and four operator's manuals to be furnished at the time of delivery \_\_\_\_\_  
12 month full service and repair warranty for cab/chassis \_\_\_\_\_
- Selected bidder shall pick up the truck chassis from a Grant County location and install the dump body, special hitch plate, air and hydraulic systems in substantial compliance with the attached schematics and plans \_\_\_\_\_

Nearest service outlet for **dump body** warranty repairs:

Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Street: \_\_\_\_\_ Phone: (\_\_\_\_) \_\_\_\_\_  
 City: \_\_\_\_\_ Fax: (\_\_\_\_) \_\_\_\_\_  
 State: \_\_\_\_\_ Zip \_\_\_\_\_ Email: \_\_\_\_\_

Proposed customer training:

Operator..... hrs @ \$ \_\_\_\_\_/hr  
 Service..... hrs @ \$ \_\_\_\_\_/hr  
 Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
 Location..... \_\_\_\_\_

**Two-way Snow Plow Specifications**

The selected bidder is required to furnish and install a two-way snow plow with hitch using controls and hydraulics provided by dump body installer.

- 2013 Model Year \_\_\_\_\_
- 10 gauge steel two-way reversible plow with quick disconnect hydraulic couplers \_\_\_\_\_
- 12' overall length, 8'11" plowing width @ 42° plow angle \_\_\_\_\_
- 40" to 46 " moldboard height @ nose \_\_\_\_\_
- 46" or taller moldboard height @ discharge end \_\_\_\_\_
- Vertical rib reinforcement per manufacturer's standard \_\_\_\_\_
- Solid integral reflector and moldboard, 2,000+ lb weight less hitch and hydraulics \_\_\_\_\_
- 6" x 5/8" high tensile steel cutting edge with carbide inserts and 6" x 1/2" high tensile steel facing edge \_\_\_\_\_
- Wear shoes, adjustable. \_\_\_\_\_
- Adjustable spring-type safety trip \_\_\_\_\_
- Heavy duty front frame hitch with hydraulic plow lift. Hitch and plow shall be capable of performing at working speed of 35 mph. Hitch must accommodate truck tilt hood. Truck chassis provided will have 24" integral front frame extensions. Installer must cut frame extensions to length, reinstall front bumper leaving sufficient space to dismount and service PTO pump \_\_\_\_\_
- All hydraulic connections must terminate with quick disconnect flush face (minimum spill) couplers and must be clearly and permanently labeled. See attached plan for Parker part numbers for 1/2" and 3/4" flush face quick couplers \_\_\_\_\_

- Electric/air-actuated controls for plow lift and two-way positioning mounted on air control console \_\_\_\_\_
- Quick disconnect couplers: 1/2" male/female must be Parker FF-502-8FP/Parker FF-501-8FP \_\_\_\_\_
- Hydraulic line used to lower snow plow must have release restriction to prevent plow drop \_\_\_\_\_
- Provide and install high-mounted headlights, turn signals and side markers to offer visibility above the mounted snow plow. Headlights, turn signals and side marker lights shall be mounted on the truck chassis. Chassis bidder to provide switch and wiring for high-mount headlights, turn signal and side marker lights used above snow plow. Chassis bidder to provide receptacle on hood near tilt pin, allowing for hood tilt. Coordinate installation with chassis provider \_\_\_\_\_
- Color: Manufacturer's standard \_\_\_\_\_
- All factory standard equipment and warranties including: Three parts books, three shop manuals, four operator's manuals to be furnished at the time of delivery \_\_\_\_\_
- 12 month full service and repair warranty for snow plow \_\_\_\_\_
- Selected bidder shall pick up the truck chassis from a Grant County location and install the snow plow, plow hitch, and hydraulic systems in substantial compliance with the attached schematics and plans \_\_\_\_\_

Nearest service outlet for **snow plow** warranty repairs:

Company: \_\_\_\_\_  
 Street: \_\_\_\_\_  
 City: \_\_\_\_\_  
 State: \_\_\_\_\_ Zip \_\_\_\_\_

Contact: \_\_\_\_\_  
 Phone: (\_\_\_\_) \_\_\_\_\_  
 Fax: (\_\_\_\_) \_\_\_\_\_  
 Email: \_\_\_\_\_

Proposed customer training:

Operator..... hrs @ \$ \_\_\_\_\_/hr  
 Service..... hrs @ \$ \_\_\_\_\_/hr  
 Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
 Location..... \_\_\_\_\_

#### **10 c.y. Body Sander Specifications**

The selected bidder is required to furnish and install a 10 cubic yard sander using controls and hydraulics provided by dump body installer.

- 2013 model year \_\_\_\_\_
- 10 gauge steel hopper with 10 cubic yard struck capacity (minimum) with replaceable bolt-on bottom and inverted "V". Side trap door for manual unloading \_\_\_\_\_
- 24" wide conveyor with 1 1/4" x 3/8" flights, and rear discharge chute for emptying sander \_\_\_\_\_
- Separate hydraulic drivers for conveyor and spinner with cab mounted controls and 3/4" Parker flush face full flow quick disconnect couplers to connect to special hitch \_\_\_\_\_
- NS200 system (Norstar Industries (253) 735-1881) to manage hydraulic flow requirements for conveyor and spinner assemblies mounted on body sander. Install In-cab controls to operate flow controller \_\_\_\_\_
- Heavy duty 18" to 20" spinner assembly mounted in front of tandem axle with four (4) adjustable deflectors and direct spreading capability. Drop chute construction to bypass truck driveline \_\_\_\_\_
- Hinged hopper screens \_\_\_\_\_
- Catwalks with side ladder on hopper and mudflaps \_\_\_\_\_
- Cab shield \_\_\_\_\_
- LED rear stop lights, park lights, turn lights \_\_\_\_\_

- One (1) front-mounted and two (2) rear-mounted Whelen L31 Super LED 360° Beacons. Use available chassis upfitter switches, provide required in-line fuses (not circuit breakers), connect highest pulse flash pattern w/high intensity feature
- Color: Manufacturer's standard
- Two parts books, two shop manuals, and two operator's manuals to be furnished at the time of delivery. CDs furnished in lieu of paper allowable
- Selected bidder shall pick up the truck chassis from a Grant County location and mount and make the sander fully operational on truck chassis bid above. The successful bidder will provide all system controls and other equipment necessary to successfully complete the installation

Additional Options: (Please list the cost to add following options for equipment listed above or add the equipment specified. Do not include sales tax. Do not include this price in the base bid)

- Stainless steel sander construction

\$

Nearest service outlet for **body sander** warranty repairs:

Company: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Street: \_\_\_\_\_ Phone: (\_\_\_\_) \_\_\_\_\_  
 City: \_\_\_\_\_ Fax: (\_\_\_\_) \_\_\_\_\_  
 State: \_\_\_\_\_ Zip \_\_\_\_\_ Email: \_\_\_\_\_

Proposed customer training:


Operator..... hrs @ \$ \_\_\_\_\_/hr  
 Service..... hrs @ \$ \_\_\_\_\_/hr  
 Mechanical. . . hrs @ \$ \_\_\_\_\_/hr  
 Location.....

*Replaces: #2200 (transfer to Landfill) [Dist 2], #2160 Thermolay [Dist 2]*

# "Typical" 12/14 CY Dump Truck used by Grant County


January 10, 2011


No Scale



Note: Several dimensions for the hitch assembly will require modification in order to match the frame rail height and width of each truck chassis manufacturer. The bar height and pintle hitch height must remain as shown.

Detail A





**TRADE-INS:**

**#1330 - 1991 Ford LT9000 w/Henke two-way 12' snow plow & Monroe 15' body sander**

VIN No. 1FDYU90XXMVA25887 License No.15871C Mileage as of 12/18/12: 254,238  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A  
transmission, 20,000 lb. front axle, 23,000 lb. rear axle, trans. mounted PTO and pump @ 35 gpm  
at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel  
tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor  
and Bendix AD-9 heated air dryer, 54,400 gvw, Red

This chassis is equipped with a Monroe 15' sander body, and a Henke two-way 12 ft snow plow.

The chassis, sander and plow may be inspected at Central Shop in Ephrata, WA., 124 Enterprise  
St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**#2160 - 1997 Ford LN8000 w/4 cy Thermolay Asphalt Patcher**

VIN No. 1FDYR82E1VVA03981 License No.37848C Mileage as of 12/18/12: 81,813  
Cummins 8.3L 6 cyl. diesel engine (210 hp), Fuller 10 speed RT7608LL transmission, 12,000 lb.  
front axle, 23,000 lb. single rear axle, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3  
bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left  
and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9  
heated air dryer, 35,000 gvw, Red

This chassis is equipped with a 4 cy Thermolay Asphalt Patcher and Spreader.

The chassis and patcher may be inspected at Dist 2 Shop in Moses Lake, WA., 12171 Road 3  
NE, Monday through Thursday between 10:00 am and 3:00 pm. (509) 765-4172

**#3300 - 1991 Ford LT9000 w/Heil 10 cy dump body**

VIN No. 1FDYU90X8MVA25886 License No.15877C Mileage as of 12/18/12: 293,564  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A  
transmission, 20,000 lb. front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35  
gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type  
fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix  
compressor and Bendix AD-9 heated air dryer, 54,400 gvw, Red

This chassis is equipped with a Heil 10-12 cy dump body.

This chassis and dump body may be inspected at Grant County Landfill in Ephrata, WA., 3803  
Neva Lake Rd NW, Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-4319

**#3510 - 1998 Peterbilt 357 w/Crysteel 12 cy dump body, Henke EXP two-way 11' snow plow**

VIN No. INPALB9X-3-WD446791 License No.43786C Mileage as of 12/18/12: 236,447  
Cat 3406-E 6 cyl. diesel engine (355 hp), Fuller RTLO-14713A 13 speed transmission, 20,000 lb.  
front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank  
control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and  
right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated  
air dryer, 54,600 gvw, Red

This chassis is equipped with a Crysteel 12 cy Dump body, a Monroe 15' sander body, and a  
Henke two-way 12 ft snow plow.

The chassis, dump body and plow may be inspected at Central Shop in Ephrata, WA., 124  
Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**#034 - 1985 International Harvester Cargostar 1950B-DT466 w/Line Striper**

VIN No. 2MTNGUXR3FCB10318 License No. 15824C Mileage as of 12/18/12: 214,792  
IH DT466 diesel engine, 466 CID (210 hp), T448 10 speed transmission, cabover, one 70 gal. fuel tank, 164" wheelbase, 146" cab/axle, 32,000 gvw, Light Green, 11R22.5 tires front and rear.

This chassis is equipped with a 3 nozzle Line Striper, an auxiliary John Deere 4239 DF 4 cylinder diesel engine, 325 gallon paint tanks, 2400 lb glass bead tank, two Vicom cameras with cab monitor.

The chassis and line striper may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

All equipment is offered "AS IS". Prospective buyers may view the equipment at the convenience of the operator. Please call the department to make arrangements to inspect the vehicle. All equipment is operating and currently in-service.

Informational Copy Only - NOT FOR BIDDING  
Call 509-754-6082 to obtain Bid Package



## Non-Collusion Declaration

**I, by signing the proposal, hereby declare, under penalty of perjury under the laws of the United States that the following statements are true and correct:**

1. That the undersigned person(s), firm, association, or corporation has (have) not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with the project for which this proposal is submitted.
2. That by signing the signature page of this proposal, I am deemed to have signed and have agreed to the provisions of this declaration.

Informational Copy Only - NOT FOR BIDDING  
Call 509-754-6082 to obtain Bid Package

**Informational Copy Only - NOT FOR BIDDING**  
Call 509-754-6082 to obtain Bid Package

## Proposal for New Equipment - Signature Page

The Bidder supplying new vehicles and trade-in offers is hereby advised that by signature of this proposal he/she is deemed to have acknowledged all requirements and signed all certificates contained herein.

No proposal guaranty is required for this bid proposal offering new vehicles and trade-in offers.

Receipt is hereby acknowledged of addendum(s) No.(s) \_\_\_\_\_, \_\_\_\_\_ & \_\_\_\_\_.

In compliance with Chapter 39.34.030(5)b RCW a public notice for this solicitation for bids has been posted on Grant County's website: <http://www.grantcountyweb.us/GCPW/index.htm>

- The Bidder will allow Grant County to purchase additional contract items at the original bid prices offered: ..... Yes \_\_\_\_\_ No \_\_\_\_\_
- The Bidder will allow other public agencies to purchase additional contract items at the original prices offered (*RCW 39.34*): ..... Yes \_\_\_\_\_ No \_\_\_\_\_
- The Bidder will allow modifications on contract items for additional purchase requests (*subject to wholesale price adjustments agreeable to each public agency*): ..... Yes \_\_\_\_\_ No \_\_\_\_\_
- The Bidder understands Grant County accepts no responsibility for the payment of any additional purchase requests made by other public agencies: ..... Yes \_\_\_\_\_ No \_\_\_\_\_
- The Bidder understands Grant County is not required to purchase additional contract items: ..... Yes \_\_\_\_\_ No \_\_\_\_\_

Signature of Authorized Official(s) \_\_\_\_\_

**PROPOSAL MUST BE SIGNED →** \_\_\_\_\_

\_\_\_\_\_  
Please Print Name of Authorized Official

Firm Name \_\_\_\_\_

Address \_\_\_\_\_

City, St, Zip \_\_\_\_\_

Voice (\_\_\_\_) \_\_\_\_\_

Fax (\_\_\_\_) \_\_\_\_\_

Email \_\_\_\_\_

State of Washington License No. \_\_\_\_\_

Federal ID No. \_\_\_\_\_

- Note:
- (1) This proposal form is not transferable and any alteration entered hereon without prior permission from the County Engineer will be cause for considering the proposal irregular and subsequent rejection of the bid.
  - (2) Should it be necessary to modify this proposal either in writing or by electronic means, please make reference to the following proposal number in your communication: **Equipment Contract 2013-02**

**Informational Copy Only - NOT FOR BIDDING**  
Call 509-754-6082 to obtain Bid Package

## CONTRACT

THIS AGREEMENT, made and entered into this \_\_\_\_\_ day of \_\_\_\_\_, 2013, between the Board of County Commissioners of Grant County, State of Washington, acting under and by virtue of Chapter 36.77 of the Revised Code of Washington, as amended, hereinafter called the County, and \_\_\_\_\_, for itself, its heirs, executors, administrators, successors and assigns, hereinafter called the Contractor.

### WITNESSETH:

That in consideration of the payments, covenants, and agreements, hereinafter mentioned, and attached and made a part of this agreement, to be made and performed by the parties hereto, and the parties hereto covenant and agree as follows:

### DESCRIPTION OF WORK:

1. The Contractor shall do all work and furnish all tools, materials, labor and equipment necessary to improve and complete **Dump Trucks, Equipment Contract 2013-02**, located in Grant County, Washington, as proposed in a bid opened **2:00 PM, Tuesday, January 8, 2013** in accordance with and as described in the herein attached plans and standard specifications, and in full compliance with the terms, conditions, and stipulations herein set forth and attached, now referred to any by such reference incorporated herein and made part hereof as fully for all purposes as if here set forth at length, and shall perform any alterations in or additions to the work covered by this contract and every part thereof and any force account work may be ordered as provided in this contract and every part thereof.
2. The Contractor shall provide and be at the expense of all materials, labor, carriage, tools, implements and conveniences and things of every description that may be requisite for the transfer of materials and for constructing and completing the work provided for in this contract and every part thereof.
3. The County hereby promises and agrees with the Contractor to employ, and does employ the Contractor to provide the materials and to do and cause to be done the above described work and to complete and finish the same according to the attached plans and specifications and the terms and conditions herein contained, and hereby contracts to pay for the same according to the attached specifications and the schedule of unit or itemized prices hereto attached, at the time and in the manner and upon the conditions provided for in this contract and every part thereof. The County further agrees to employ the Contractor to perform any alterations in or additions to the work covered by this contract and every part thereof and any force account work that may be ordered and pay for same under the terms of this contract and the attached plans and specifications.
4. The Contractor for himself, and for his heirs, executors, administrators and assigns, and successors and assigns, does hereby agree to the full performance of all the covenants herein contained upon the part of the Contractor.
5. It is further provided that no liability shall attach to the County by reason of entering into this contract, except as expressly provided herein.

IN WITNESS WHEREOF, the said Contractor has executed this instrument, and the said Board of County Commissioners of aforesaid County has caused this instrument to be executed by and in the name of said Board by its Members, duly attested by its Clerk, the day and year first above written, and the seal of said Board to be hereunto affixed on the date in this instrument first above written.

\_\_\_\_\_, 2013

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Print Name

\_\_\_\_\_  
Firm Name

\_\_\_\_\_  
Address

(County Seal)

\_\_\_\_\_  
City State Zip

( ) \_\_\_\_\_  
Phone

ATTEST:

\_\_\_\_\_  
Clerk of the Board

APPROVED AS TO FORM:

\_\_\_\_ day of \_\_\_\_\_, 2013

\_\_\_\_\_  
Deputy Prosecuting Attorney

BOARD OF COUNTY COMMISSIONERS  
OF GRANT COUNTY, WASHINGTON

\_\_\_\_\_  
Chairman

\_\_\_\_\_  
Commissioner

\_\_\_\_\_  
Commissioner

## **PROPOSAL - PART II**

(For Used Equipment Bidders)

### **General Conditions**

The attached specifications are for the purpose of providing details regarding the type of equipment available for sale by sealed bids.

Bidders interested in bidding for used equipment must complete and return Part II of this proposal.

The bidders are advised that mileage/hours on used equipment will continue to accumulate until replacement vehicles/equipment are delivered.

The successful bidder shall pay State and local sales and use taxes on all products purchased. The Bidder shall not include state and local taxes in the bid price in the space provided..

### **Bid Evaluations**

Bid evaluations shall include, but not be limited by, the following criteria:

- Price
- Bid prices shall be compared to trade-in offers provided by vendors bidding new equipment.
- Grant County receives a reduction in sales tax from trade-in offers included with new equipment. That sales tax reduction shall be considered when comparing offers made by bidders for used equipment.
- Although no minimum bids are reserved Grant County will compare trade-in offers to reliable publications or other sources. Bids considered too low will not be accepted.
- Public's best interest.

### **Submissions**

Bidders are advised to submit the following with each bid item:

- A 5% security in the form of a certified or cashier's check based upon the bidder's offer for the used equipment.
- Completed and signed Proposal sheet. Failure to complete and sign the Proposal form may result in the bid being declared irregular and not considered.

The Bidder may submit any other information that may assist Grant County in evaluating the bid.

### **Warranty**

The Bidder is advised Grant County offers no express or implied warranty and all used equipment available for sale is offered "AS IS". Prospective buyers may view the equipment at the convenience of the operator. Contact information is listed.

### **Trade-ins**

Grant County is not obligated to accept any trade-in offer. The trade-in offer itself will be for used equipment and described attachments, if any. All bids for trade-ins using Part II of this proposal will be considered separately. The successful bidder shall be given the prescribed number of days shown in the Proposal Signature Page from the date of notification that the used equipment is available and to pay the balance owed and pickup the equipment. If the bidder fails to complete the transaction within that time period the deposit shall be forfeited to Grant County.

The available list of used equipment follows:

## TRUCKS

### **#1330 - 1991 Ford LT9000 w/Henke two-way 12' snow plow & Monroe 15' body sander**

VIN No. 1FDYU90XXMVA25887 License No.15871C Mileage as of 12/18/12: 254,238  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A  
transmission, 20,000 lb. front axle, 23,000 lb. rear axle, trans. mounted PTO and pump @ 35 gpm  
at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel  
tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor  
and Bendix AD-9 heated air dryer, 54,400 gvwt, Red

This chassis is equipped with a Monroe 15' sander body, and a Henke two-way 12 ft snow plow.

The chassis, sander and plow may be inspected at Central Shop in Ephrata, WA., 124 Enterprise  
St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**Amount offered: \$** \_\_\_\_\_

### **#2160 - 1997 Ford LN8000 w/4 cy Thermolay Asphalt Patcher**

VIN No. 1FDYR82E1VVA03981 License No.37848C Mileage as of 12/18/12: 81,813  
Cummins 8.3L 6 cyl. diesel engine (210 hp), Fuller 10 speed RT7608LL transmission, 12,000 lb.  
front axle, 23,000 lb. single rear axle, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3  
bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left  
and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9  
heated air dryer, 35,000 gvwt, Red

This chassis is equipped with a 4 cy Thermolay Asphalt Patcher and Spreader.

The chassis and patcher may be inspected at Dist 2 Shop in Moses Lake, WA., 12171 Road 3  
NE,  
Monday through Thursday between 10:00 am and 3:00 pm. (509) 765-4172

**Amount offered: \$** \_\_\_\_\_

### **#3300 - 1991 Ford LT9000 w/Heil 10 cy dump body**

VIN No. 1FDYU90X8MVA25886 License No.15877C Mileage as of 12/18/12: 293,564  
Cat 3406-B 6 cyl. diesel engine (330 hp), Fuller 13 speed Road Ranger RTO14613A  
transmission, 20,000 lb. front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35  
gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type  
fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix  
compressor and Bendix AD-9 heated air dryer, 54,400 gvwt, Red

This chassis is equipped with a Heil 10-12 cy dump body.

This chassis and dump body may be inspected at Grant County Landfill in Ephrata, WA., 3803  
Neva Lake Rd NW, Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-4319

**Amount offered: \$** \_\_\_\_\_



**#3510 - 1998 Peterbilt 357 w/Crysteel 12 cy dump body, Henke EXP two-way 11' snow plow**

VIN No. INPALB9X-3-WD446791 License No. 43786C Mileage as of 12/18/12: 236,447  
Cat 3406-E 6 cyl. diesel engine (355 hp), Fuller RTLO-14713A 13 speed transmission, 20,000 lb. front axle, 23,000 lb. rear axles, trans. mounted PTO and pump @ 35 gpm at 2000 rpm, 3 bank control valve set, 40 gal. hydraulic oil reservoir, two 50 gal. step type fuel tanks mounted left and right sides, 162" wheelbase, 96" cab/axle, 13.2 cfm Bendix compressor and Bendix AD-9 heated air dryer, 54,600 gvwt, Red

This chassis is equipped with a Crysteel 12 cy Dump body, a Monroe 15' sander body, and a Henke two-way 12 ft snow plow.

The chassis, dump body and plow may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**Amount offered: \$** \_\_\_\_\_

**#034 - 1985 International Harvester Cargostar 1950B-DT466 w/Line Striper**

VIN No. 2MTNGUXR3FCB10318 License No. 15824C Mileage as of 12/18/12: 214,792  
IH DT466 diesel engine, 466 CID (210 hp), T448 10 speed transmission, cabover, one 70 gal. fuel tank, 164" wheelbase, 146" cab/axle, 32,000 gvwt, Light Green, 11R22.5 tires front and rear.

This chassis is equipped with a 3 nozzle Line Striper, an auxiliary John Deere 4239 DF 4 cylinder diesel engine, 325 gallon paint tanks, 2400 lb glass bead tank, two Vicom cameras with cab monitor.

The chassis and line striper may be inspected at Central Shop in Ephrata, WA., 124 Enterprise St. S.E., Monday through Thursday between 10:00 am and 3:00 pm. (509) 754-6086

**Amount offered: \$** \_\_\_\_\_

All equipment is offered "AS IS". Prospective buyers may view the equipment at the convenience of the operator. Please call the department to make arrangements to inspect the vehicle. All equipment is operating and currently in-service.

## Proposal for Trade-ins - Signature Page

The Bidder for trade-in vehicles only (not including new vehicle dealers) is hereby advised that by signature of this proposal he/she is deemed to have acknowledged all requirements and signed all certificates contained herein.

A 5% proposal guarantee is required for the bid proposal for trade-ins.  
(Please attach cashier's check or certified check.)

Receipt is hereby acknowledged of addendum(s) No.(s) \_\_\_\_\_, \_\_\_\_\_ & \_\_\_\_\_.

Additional terms:

1. If the Bidder's offer to purchase used equipment is accepted by the County, the bidder understands he/she has 30 days to complete the sale after notification of the delivery of new vehicle.
2. The Bidder may be allowed to withdraw his/her offer if the used vehicle is damaged or has become mechanically unreliable and the value of used vehicle is reduced. In the event this happens the County and the Bidder may negotiate a new purchase price.
3. The bidder will not be permitted to withdraw his/her offer do to increased mileage or hours.

Signature of Authorized Official(s) \_\_\_\_\_

**PROPOSAL MUST BE SIGNED →** \_\_\_\_\_

\_\_\_\_\_  
Please Print Name of Authorized Official

Firm Name \_\_\_\_\_

Address \_\_\_\_\_

City, St, Zip \_\_\_\_\_

Voice (\_\_\_\_) \_\_\_\_\_

Fax (\_\_\_\_) \_\_\_\_\_

Email \_\_\_\_\_

- Note:
- (1) This proposal form is not transferable and any alteration entered hereon without prior permission from the County Engineer will be cause for considering the proposal irregular and subsequent rejection of the bid.
  - (2) Should it be necessary to modify this proposal either in writing or by electronic means, please make reference to the following proposal number in your communication: **Equipment Contract 2013-02**